

Wanaka Dual Outlet

500/600/800 GPD All-in-one RO Water Purifier

The superior option to tap water, this premium four-stage reverse osmosis system delivers top-quality drinking water right to you. Its advanced contaminant removal makes it perfect for drinking and cooking. Wanaka provides clean, refreshing water at a constant flow rate for residential and light commercial use. Easy to operate and reliable. Low operating cost.



2 L/min
Flow Rate



1.5 : 1
Drain Ratio



Dual
Water Outlet



3 Seconds
Filter-Change

Tankless

More compact, and produce fresher water. Taking up less space and purifying water as it is needed.

Slim & Stylish

Compact design allows it to be installed under the sink or over the counter top. Its design will not affect the interior style.

Long-lifetime Purification

The RO filter lasts up to 36 months. Removes 99% of contaminants from incoming water supply.

Care Free

System performance indicators. Leakage protection includes overwork protection, and external leak protector.

Key Contaminants Removed:

particulates, chlorine, chromium, arsenic, virus, bacterial, phenol, pesticides, mercury, heavy metals, E.coli (97%)



Dual Water Outlet

Fast and stable water supply:
RO Purified water, Filtered water.



Filter-Change Reminder

Check filter status on display
or the faucet at anytime.



3 Seconds Filter-Change

Utilizes pull-and-push sanitary
filters for easy replacements.

Specifications



Model	J3378-ROB120a	J2806-ROB90	J2865-ROB75
Water Capacity	800 GPD	600 GPD	500 GPD
RO Purified Water Flow Rate	120 L/h	90 L/h	75 L/h
Filtered Water Flow Rate	240 L/h	180 L/h	180 L/h
Inlet Water Temperature	5-38°C	5-38°C	5-38°C
Inlet Water Pressure	100-300 kPa	100-300 kPa	100-300 kPa
Filter & Service Life*	CFII Composite filter, 12 months	CFII Composite filter, 12 months	US Composite filter 2.0, 12 months
	CFII Composite filter, 12 months	RO Filter, 36 months	RO Filter, 36 months
	RO Filter, 36 months	AC Filter, 12 months	AC Filter, 12 months
Faucet Included	2-Handle lead-free stainless steel faucet		
Voltage/Frequency	220 V/50 Hz	220 V/50 Hz	220 V/50 Hz
Power Consumption	80 W	60 W	60 W
Dimensions (mm)	W 446 x D 164 x H 436		
Weight	10 Kg	10 Kg	10 Kg
QTY/ Container	20 GP: 418 pcs 40 GP: 845 pcs 40 HQ: 994 pcs		

* Service life will vary according to flow rate, influent line pressure and local water conditions.